

PRODUCT CODE:

CPVC SHEET

2416

COLOUR:

GREY


SHEET SIZE:

48" X 96"

STOCK NUMBER	THICKNESS INCHES	LBS/SHEET APPROX.
2416 0015 5199	1/64	4.2
2416 0031 4896	1/32	8.4
2416 0125 4896	1/8	33
2416 0187 4896	3/16	50
2416 0250 4896	1/4	65
2416 0375 4896	3/8	98
2416 0500 4896	1/2	130
2416 0750 4896	3/4	195
2416 1000 4896	1	260
2416 1250 4896	1-1/4	325
2416 1500 4896	1-1/2	390
2416 2000 4896	2	520

PROPERTIES

- High heat resistance.
- Excellent corrosion resistance.
- Easily fabricated.
- Will not support combustion.
- Good electrical insulation.
- Cementable.
- Weldable.



TYPICAL APPLICATIONS

- Chemical tanks
- Spacers
- Drip racks
- Stiffeners
- Waste treatment
- Insulators

- Tolerance: +/-10% (Thickness).
- Inquire about our cut to size abilities.
- CPVC is Type IV Normal Impact, high temperature corrosion resistant Chlorinated Polyvinyl Chloride with a smooth industrial finish.
- Complies with ASTM specification D 1784 (Class 23447-B).



PRODUCT CODE:

CPVC ROD

2422

COLOUR:

GREY


STANDARD LENGTH:

10 FEET

STOCK NUMBER	DIAMETER INCHES	LBS/FT APPROX.
2422 0500	1/2	0.134
2422 0750	3/4	0.283
2422 1000	1	0.540
2422 1250	1-1/4	0.800
2422 1500	1-1/2	1.250
2422 2000	2	2.000
2422 2250	2-1/4	2.627
2422 2500	2-1/2	3.243
2422 3000	3	4.860
2422 3500	3-1/2	3.358
2422 4000	4	8.640
2422 5000	5	12.98

PROPERTIES

- Chemically resistant.
- Readily machined.
- High temperature.
- Cementable.
- Weldable.



TYPICAL APPLICATIONS

- Fittings
- Bushings
- Valves
- Spacers
- Pump components
- Caps
- Flanges

- Tolerance: Oversized diameter.

